

OCTAN REMOTE

Datasheet



The NodOn® Octan Remote can directly control any kind of Z-Wave® or Z-Wave Plus® compliant devices such as NodOn® Smart Plug or trig scenes through a Z-Wave® or Z-Wave Plus® Home Automation Gateway (Gateway Mode). The Octan Remote is magnetic and can be fixed on any kind of metallic area but it is also delivered with its wall mounting plate which can be easily installed on a wall.

TECHNICAL DATA

Power supply: CR2032 battery – 1.5 to 2 years lifetime

4 buttons

Wall support mounting using adhesive bonding (included) or screws (not included)

Embedded magnet for metallic surface or support sticking

Operational temperature – 0°C to 40°C - Altitude – 2.000m

Radio protocol Z-Wave®: 868.4MHz – 500 Series – Compliant Z-Wave Plus® SDK 06.51.06

Range: 40m indoor / 80m outdoor

Dimensions: 80*80*17.5mm (with support) 75*46*11.5mm (Remote only)

Warranty 2 years

STANDARDS

EN 60950-1:2006 +A11:2009 + A1:2010 + EN301 489-1 V1.9.2

A12:2011 + A2:2013

EN301 489-3 V1.6.1

EN 300 220-2 V2.4.1

EN 62479:2010

REFERENCE NUMBER

CRC-3-1-00 - EAN : 3700313920282 - White